

HEAVY DUTY AMERICAN DESIGN RECIPROCATING PISTON AIR COMPRESSOR



HD200M-WP500



2HD200M-WP500 DUPLEX

T-32 INDUSTRIAL MULTI-STAGE (PET BOTTLE) BASE-MOUNTED AIR COMPRESSOR

Model	Pump	Capacity		Bore			Stroke	Pressure		Displacement		Free Air Delivery		Tank
		Hp	kW	1st	2nd	3rd		inches	PSI	Bar	L / min	CFM	L / min	
HD30M-WP500	H0121	3.0	2.2	3.0"	1.25"		2.75"	500	34.5	170	6.0	136	4.8	SKID
HD75M-WP500	H0721	7.5	5.5	5.0"	2.0"		4.0"	500	34.5	560	20.0	445	15.7	SKID
HD100M-WP500	H0721	10.0	7.5	5.0"	2.0"		4.0"	500	34.5	710	25.0	612	21.6	SKID
HD150M-WP900		15.0	11.0				4.0"	900	62.0	690	24.6	595	21.0	SKID
HD200M-WP500	H1031	20.0	15.0	5.5"	3.0"	1.625"	4.0"	500	34.5	1400	49.5	1,104	39.0	SKID
HD200M-WP800	H1031	20.0	15.0	5.5"	3.0"	1.625"	4.0"	800	55.0	1286	45.4	1019	36.0	SKID
HD200M-WP1000	H1031	20.0	15.0	5.5"	3.0"	1.625"	4.0"	1000	69.0	1082	38.2	906	32.0	SKID

AIRGENS - HEAVY DUTY AIR COMPRESSOR FEATURES AS FOLLOWS:

- ➔ INDIVIDUAL CAST IRON CYLINDER WITH RADIAL FINS
- ➔ EFFICIENT AIR-COOLED FINNED INTER-COOLER AND AFTER-COOLER
- ➔ DUAL CONTROL AUTO-START/STOP OR LOAD/UNLOAD CONTROL
- ➔ HEAT TREATED STAINLESS STEEL CONCENTRIC RING VALVES
- ➔ LOW OIL LEVEL SWITCH PROTECTION

Note: Due to constant engineering improvements, designs and specifications are subject to change without prior notice.

- * Direct On Line Starter for Compressor 10HP and below and Star-Delta Starter for Compressor 15HP and above as standard.
- * Tank-mounted units and Duplex Compressor is also available upon request.
- * Airgens Multi-Stage Compressor comes complete with Semi-enclosed wire beltguard.
- * Improved Large efficient After-Coolers with Automatic Drain providing Low Discharge Temperatures.