

AIR RECEIVER TANK



MODEL	OUTSIDE	SHELL	OVERALL	CONNECTION	DRY	WORKING
	DIAMETER	LENGTH	LENGTH	HOLE	WEIGHT	PRESSURE
LITRES	mm	mm	mm	INCHES	(KG)	PSI
50H	286	745	938	1/2" & 1/4" SOCKET	31	150
100H	326	915	1103	1/2" & 3/8" SOCKET	47	150
180H	411	1220	1475	3/4" & 1/2" SOCKET	80	150
230H	457	1200	1460	1" & 1/2" SOCKET	190	200
350H	508	1499	1687	1-1/4" SOCKET	210	200
400H	511	1524	1830	2 X 1" SOCKET	150	150
250H-HP	459	1220	1500	2 X 1" SOCKET	225	580
400H-HP	511	1524	1830	2 X 1" SOCKET	315	580



MODEL	OUTSIDE	SHELL	OVERALL	CONNECTION	DRY	WORKING
	DIAMETER	LENGTH	LENGTH	HOLE	WEIGHT	PRESSURE
LITRES	mm	mm	mm	INCHES	(KG)	PSI
220V	490	815	1236	1" & 3/4" SOCKET	170	200
250V	559	790	1275	2" SOCKET	160	200
270V	590	762	1232	1" & 3/4" SOCKET	160	200
400V	508	1525	1968	2" SOCKET	350	145
500V	558	1720	2243	2" SOCKET	170	145
750V	605	1830	2370	2" SOCKET	200	145
1000V	765	1835	2481	2" SOCKET	345	145
1500V	930	1830	2580	3" FLANGE	600	145
2000V	930	2440	3190	3" FLANGE	715	145
500V-HP	600	1524	2045	2 X 2" SOCKET	390	580
1000V-HP	765	1930	2626	2 X 2" SOCKET	820	580

Remarks : Other capacity and working pressure can be custom made according to customers' request.