

BAR CODE ITEM PART NO	PRODUCT PHOTO	DESCRIPTION & SPECIFICATION
--------------------------	------------------	--------------------------------

HIGH TIMING ACCURACY / SIMPLE AND COMPACT STRUCTURE / RELIABLE PERFORMANCE & LONG ENDURANCE

<p>AIRGENS XY-720 1/2" 16 BAR ELECTRONIC TIMER DRAIN</p>  <p style="text-align: center; font-weight: bold;">1413012061001</p>		<p>TIMER DRAIN C/W STRAINER</p> <p>Port Size : Femele G ½"</p> <p>Max operation pressure : 1 – 16 bar</p> <p>Body Material : Brass</p> <p>Seal ring material : NBR</p> <p>Max Media Temperature: 80 °C</p> <p>Interval time : 0.5 – 45 mins, adjustable</p> <p>Discharge time : 0.5 – 10 seconds, adjustable</p> <p>Ambient Temperature : -20 to +60 °C</p> <p>Voltage : 110 / 230 VAC</p>
<p>AVC TDCS728A 1/2" 16BAR ELECTRONIC TIMER DRAIN C/W STRAINER (0200D)</p>  <p style="text-align: center; font-weight: bold;">1413010423001</p> <p>AVC TDCS728BV 1/2" 16BAR 20VA ELECTRONIC TIMER DRAIN C/W STRAINER</p>  <p style="text-align: center; font-weight: bold;">1413010423002</p>	 <p style="text-align: center;">CS-728 With Ball Valve</p>	<p>TIMER DRAIN C/W BALL VALVE & STRAINER</p> <p>Port Size : Female G ½"</p> <p>Max operation pressure : 1 – 16 bar</p> <p>Body Material : Brass</p> <p>Seal ring material : NBR</p> <p>Max Media Temperature: 80 °C</p> <p>Interval time : 0.5 – 45 mins, adjustable</p> <p>Discharge time : 0.5 – 10 seconds, adjustable</p> <p>Ambient Temperature : -20 to +60 °C</p> <p>Voltage : 110 / 230 VAC</p>
<p>AIRGENS DM-100T 1/2" DRAIN MASTER CONDENSATE DRAIN TIMER (16BAR)</p>  <p style="text-align: center; font-weight: bold;">1413011425001</p>		<p>JORC TIMER DRAIN C/W STRAINER</p> <p>Max operation pressure : 40 bar</p> <p>Body Material : Brass</p> <p>Seal ring material : NBR</p> <p>Max Media Temperature: 80 °C</p> <p>Interval time : 0.5 – 45 mins, adjustable</p> <p>Discharge time : 0.5 – 10 seconds, adjustable</p> <p>Ambient Temperature : -20 to +60 °C</p>
<p>AIRGENS DM-100T 1/2" DRAIN MASTER CONDENSATE DRAIN TIMER (16BAR)</p>  <p style="text-align: center; font-weight: bold;">1413011425001</p>		<p>DRAIN MASTER- TIMER</p> <p>Max Capacity (l / hr) : 650</p> <p>Operating Pressure : 0.8 bar ~ 16 bar</p> <p>Temperature (C°) : 2 ~ 80</p> <p>Condensate Inlet : 1/2"</p> <p>Condensate Discharge : 1/2"</p> <p>Weight (kg) : 0.7</p> <p>Voltage : 110 / 230Vac / 50 - 60Hz / 1PH / 2VA</p> <p>Dimension (mm) : (H) 148 x (L) 107 x (W) 90</p>
<p>AIRGENS DM-5N DRAIN MASTER CONDENSATE AUTO DRAIN TRAP ELECTRIC</p>  <p style="text-align: center; font-weight: bold;">1413011425002</p> <p>AIRGENS DM-15 DRAIN MASTER CONDENSATE AUTO DRAIN TRAP ELECTRIC</p>  <p style="text-align: center; font-weight: bold;">1413011425003</p>		<p>DRAIN MASTER - ZERO LOSS (MINIMAL AIR LOSS CONDENSATE DRAIN TRAP)</p> <p>Equipped with Electrostatic Capacity Sensor</p> <p>Compressor Capacity: 5m³/min to 1500m³/min</p> <p>Operating Pressure : 0.8 ~ 16 bar</p> <p>Voltage AC(V): Free Voltage 110, 220</p> <p>Application : Oil Injection / Oil Free</p> <p>Temperature : + 1 ~ 80° C</p> <p>Inlet / Outlet (inch) : 1/2"</p> <p>Housing Material : Aluminium , Hardcoated</p> <p>Main Function : Minimal Air Leakage ensuring economical operation at minimum cost.</p>

<p>AD402 FLOAT TYPE AUTO-DRAIN</p>  <p>1413021290001</p>		<p>FLOAT TYPE AUTO-DRAIN</p> <p>Port size: ½" BSP in Max Pressure : 10 BAR Max Temperature : 60°C</p>
<p>EXTERNAL AUTO DRAIN - 1/2" HAD 20B (FOR GPH150 FILTER)</p>  <p>1413021420002</p>		<p>BALL TYPE AIR TRAP</p> <p>Aluminum alloy mold body. Corrosion resistance to synthetic lubricant. Max. pressure : 20 bar (kg/cm²) Max. Working Temp. : 100 °C Port size: ½" BSP in/out</p>
<p>EXTERNAL AUTO DRAIN - 1/2" EAD 160B</p>  <p>1413021420003</p>		<p>BOMB TYPE AIR TRAP</p> <p>Stainless steel ball Aluminum alloy mold body. Max. pressure : 16 bar (kg/cm²) Max. Working Temp. : 100 °C Port size: ½" BSP in/out</p>
<p>STAINLESS STEEL (42 BAR) MECHANICAL AIR DRAIN TRAP (ADT-1/2")</p>  <p>1413022520006</p>		<p>AIR TRAP - 'Y' STRAINER</p> <p>Size : ½" or 1" Internal tread Max. Temperature : 400 °C Material of valve body : Stainless Steel Dimension [LxH1xH2xW] : 78 x 41 x 58 x 49 Max. Working Pressure : 42 bar</p>
<p>ACE MECHANICAL (ZERO PURGE) DRAIN TRAP P-AIR & GAS TRAPPING (ACE-15N)</p>  <p>1413021420008</p>		<p>ACE TRAP (ZERO AIR LOSS)</p> <p>Inlet : 1/2 Inch / 3/4 inch Outlet : 3/8 Inch / 1/2 inch Height : 105 mm / 109 mm & Length : 186 mm / 210 mm Range of Pressure : 3 ~ 9.9 / 10 ~ 16 (kg/cm²) Temperature : 0~60° C Capacity (l/hr) : 3 ~ 15 / 6 ~ 30 Application (m³/min) : 50 / 130 Weight (kg) : 1.2 / 2.3</p>
<p>"WOORI TECH" ZERO LOSS AUTO DRAIN (WR DT-500)</p>  <p>1413022062001</p>		<p>ZERO LOSS AUTO-DRAIN</p> <p>Max Liquid Temperature : 75 °C Max Temperature : 9.9 Kg/cm² Capacity : 120 l/hr Air Comp : 100 HP</p> <p>Advantages :-</p> <ul style="list-style-type: none"> ▶ Zero Air Loss ▶ Low Maintenance ▶ Large Discharge Outlet ▶ Able to see the condensate level ▶ No Power Required ▶ Easy Maintenance ▶ Simple Operations