

# ELECTRIC STACKER

## AES SERIES



## ELECTRIC STACKER

Full Electric Stacker with different loading capacities and various lifting heights is built for stacking in intensive applications in stores and factories, applications that require durable high capacity trucks that are also capable of horizontal transport purposes. s

MODEL NO:	AES	10,15,20/16	10,15,20/20	10,15,20/25	10, 15/30
Drive Unit		ELECTRIC	ELECTRIC	ELECTRIC	ELECTRIC
Load Capacity (kg)		1000 / 1500 / 2000			1000 / 1500
Load Center (Q, mm)		550	550	550	550
Mast Form		Single Cylinder	Double / Double Cylinder		
Front Wheel Dimension (mm)		Φ 80 X 60	Φ 80 X 60	Φ 80 X 60	Φ 80 X 60
Rear Wheel Dimension (mm)		Φ 130 X 55	Φ 130 X 55	Φ 130 X 55	Φ 130 X 55
Traction Wheel (mm)		Φ 250 X 80	Φ 250 X 80	Φ 250 X 80	Φ 250 X 80
Fork Dimension (L3, mm)		1220 x 160 x 50		1220 x 160 x 50	
Lifting Height (mm)		1600	2000	2500	3000
Extended Height (H3, mm)		2080	2500	3000	3500
Closed Height (H1, mm)		2080	1580	1850	2080
Fork Clearance from Ground (H5, mm)		80-90	80-90	80-90	80-90
Total Length (L1, L2 mm)		2070, 2300	2070, 2300	2070, 2300	2070, 2300
Total Width (B, mm)		815	815	815	815
Maximum Fork Width (B1, mm)		680	680	680	680
Turning Radius {Open Pedal} (R1, mm)		1600	1600	1600	1600
Truck Weight {Without Battery} (kg)		780	880	930	980
Battery Charger		AC220V/50HZ / DC24V/40A		AC220V/50HZ / DC24V/40A	