

SEMI-ELECTRIC STACKER



Model Number	ASES				
	1.0/16	1.0/20	1.0/25	1.0/30	1.0/33
Capacity (kg)	1000				
Lifting Height H2 (mm)	1600	2000	2500	3000	3300
Mast Type	Single	Double			
Fork Length L1 (mm)	1000				
Min. Height of Fork H1 (mm)	90				
Load Center (mm)	500				
Charging Voltage	AC220V				
Motor Power	1.6KW				
Outer Width of Legs (mm)	635				
Inner Width of Legs (mm)	395				
Adjustable Width of Forks (mm)	360 - 690				
Rear Wheel Size (mm)	Φ 80 X 93				
Front Wheel Size (mm)	Φ 80 X 65				
Weight (kg)	280	305	325	350	410
Closed Height H3 (mm)	2080	1650	1900	2150	2300
Extended Height (mm)	2080	2650	3125	3625	3925

	1.5/16	1.5/20	1.5/25	1.5/30	1.5/33
Capacity (kg)	1500				
Lifting Height H2 (mm)	1600	2000	2500	3000	3300
Mast Type	Single	Double			
Fork Length L1 (mm)	1000				
Min. Height of Fork H1 (mm)	90				
Load Center (mm)	500				
Charging Voltage	AC220V				
Motor Power	1.6KW				
Outer Width of Legs (mm)	635				
Inner Width of Legs (mm)	395				
Adjustable Width of Forks (mm)	360 - 690				
Rear Wheel Size (mm)	Φ 80 X 93				
Front Wheel Size (mm)	Φ 80 X 65				
Weight (kg)	305	350	365	415	420
Closed Height H3 (mm)	2080	1650	1900	2150	2300
Extended Height (mm)	2080	2650	3125	3625	3925

	2.0/16	2.0/20
Capacity (kg)	2000	
Lifting Height H2 (mm)	1600	2000
Mast Type	Single	Double
Fork Length L1 (mm)	1000	
Min. Height of Fork H1 (mm)	90	
Load Center (mm)	500	
Charging Voltage	AC220V	
Motor Power	1.6KW	2.0KW
Outer Width of Legs (mm)	635	
Inner Width of Legs (mm)	395	
Adjustable Width of Forks (mm)	360 - 690	
Rear Wheel Size (mm)	Φ 80 X 93	
Front Wheel Size (mm)	Φ 80 X 65	
Weight (kg)	310	415
Closed Height H3 (mm)	2080	1650
Extended Height (mm)	2080	2650

NOTE: ECONOMY FULLY AUTO HAND STACKER (TO ADD IN DC DRIVE MOTOR)